I-Ring[™]Pupil Expander Usage Guide



Introduce the I-Ring into the Anterior Chamber

.

1 Introduce the Inserter through the primary incision after injecting viscoelastic into the Anterior Chamber. Position the tip centrally over the lens and introduce the I-Ring.



2

Completely retract the prongs (a) before removing the Inserter (b) from the primary incision.




Engage the I-Ring to the Iris



Use a Sinskey Hook to secure the distal channel to the iris.




Next secure the proximal channel to the iris.




Continue to secure the two lateral channels to the iris.

Remove the I-Ring from the eye




Use a Sinskey Hook to disengage the distal channel and place it onto anterior iris.



Next disengage the proximal channel and place it onto anterior iris. Proceed to disengage the two lateral channels.



With the Inserter in the Anterior Chamber, extend the prongs over the I-Ring before positioning the cannula platform under the hinge.





Capture the hinge between the prongs of the Inserter.



5 Completely draw the I-Ring into the Inserter before withdrawing from the primary incision.



Beaver-Visitec International, Inc. 411 Waverley Oaks Road, Waltham, MA 02452 Tel: 1.866.906.8080 Fax: 1.866.906.4304 www.beaver-visitec.com Beaver-Visitec International, Sales Limited 85c Park Drive, Milton Park, Abingdon, Oxfordshire, OX14 4RY, UK Tel: 44.1865.601.256 Fax: 44.1865.595.761



US patent # 8,900,136. Additional US and International patents pending. BVI, BVI Logo and all other trademarks are property of Beaver-Visitec International (BVI) © 2015 BVI 590109-1115