



7000

Dual-Purpose Exam Chair and
Minor Procedure Table

Look closer. See further.

 **HAAG-STREIT**
RELIANCE

7000

Dual-Purpose Exam Chair and Minor Procedure Table



Ergonomic Features

Dual-side operation allows you to control chair from both sides while maintaining patient contact.

Adjustable concave headrest provides superior head and neck support, and locks with a single hand.

Upholstered armrests lock in place and release on both chair sides for security and comfort.

Large hinged footrest supports patient's full weight and tilts out of the way to save space.

Corded footswitch provides hands-free operation of chair base and top. Dual rotation locks allow you to swivel chair 340°.

Perfect for Minor Procedures

The 7000 chair reclines nearly flat for minor procedures. Non-articulating pillow headrest.

Power Hydraulic base

Square pedestal base provides crucial patient stability and superior accessibility. Finger switches and a corded footswitch raise, lower or recline chair into any position without breaking patient contact. High and low base models available.

Ultra-Durable Membrane Switches

Programmable backlit membrane switches last 10-times longer than their mechanical counterparts. They're also safer because they run at low voltages.

Finishes and Upholstery

- Hand-sewn upholstery covers high-density foam that lasts for years.
- Removable cushions for easy cleaning or replacement.
- Designer-style cushions standard.
- Base available in #20 Pearl.
- 6 standard vinyl colors and endless custom selections.

The Mark of Quality

The 7000 has passed all rigorous testing by ETL certification to assure its safety and durability, achieving ETL, C/US certificate of compliance.

Dimensions and Specifications

Base: 22 $\frac{5}{16}$ " x 24 $\frac{1}{2}$ ". Overall width: 24 $\frac{1}{2}$ ". Overall depth (excluding headrest): 36". Table position: 60". Seat: 19" wide by 18 $\frac{1}{2}$ " deep. Armrest distance: 19". Choice of two base heights. High: 22 $\frac{3}{4}$ " lowered, 33 $\frac{3}{8}$ " raised. Low: 20 $\frac{1}{4}$ " lowered, 28 $\frac{3}{4}$ " raised. Shipping weight: 325 lbs. Standard electrical: 120 volts, 50/60 Hz, 9.0 amperes total. Optional: 220-240 volts, 50/60 Hz, 4.0 amperes.